2008 BMW F 800 GS

Brake System

Front Brakes

Front Rotor Rear Brake

Rear Rotor

Acutation Method

BMW

4 Piston Caliper x 2 11.8 inch Dual Rotors

10.4 inch single Rotor

Hydraulic, DOT 4 Fluid

2 Piston Caliper

MSRP: \$10,520.00* Destination charge (not included in MSRP): \$475

Copyright 2007 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.

* Actual Price determined by dealer. Price excludes taxes, license, options and handling charge.

Prices and specifications subject to change without notice.



Engine		Wheels and Tires	
Туре	Water cooled twin cylinder 4 stroke	Front Wheel	2.15 x 21 spoked wheel with aluminum rim
Bore x Stroke	82mm x 75mm	Rear Wheel	4.25 x 17 spoked wheel with aluminum rim
Displacement	798 cc	Front Tire	90/90-21
Horsepower	85 bhp @ 7500 rpm	Rear Tire	150/70-17
Torque	62 lb/ft @ 5750 rpm	Dimensions	
Compression Ratio	12.0 : 1	Overall Length	91.0 inches
Valve Gear	DOHC, chain-driven with cam followers	Overall Width	34.2 inches
Valves	2 x 32mm intake / 2 x 27.5mm exhaust	Wheelbase	62.1 inches
Valves / Cylinder	4	Ground Clearance	N/A
Engine Oil Capacity	N/A	Seat Height	33.5 - 34.6 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	64 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.6 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	392 lbs
Fuel Capacity	4.2 gallons	Weight - Wet	455 lbs
Charging System	400 Watts @ 14 Volts	Maximum Load	975 lbs
Battery	12 Volts 14 Amps/hour	Standard Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code Price	Description
Drvietrain		N25 N/C	Dark Magnesium Metallic
Primary Drive	1.94	N33 N/C	Sunset Yellow
Clutch	Wet multi plate	Standard Equipment	
1st Gear Ratio	2.46		
2nd Gear Ratio	1.75	Avaliable Equip	ment
3rd Gear Ratio	1.38	430 \$475	Comfort Package
4th Gear Ratio	1.17	519 PKG	Heated Grips
5th Gear Ratio	1.04	539 PKG	On Board Computer
6th Gear Ratio	0.96	524 \$890	ABS
Final Drive System	Chain	588 \$60	Clear Turn Signal Lenses
Final Drive Ratio	1:2.6	603 \$235	Anti Theft Alarm
Frame and Suspension		636 \$150	Center Stand
Frame and Suspension	Tubular steel frame with a semi stressed engine	774 N/C	Low Seat
Front Suspension	45mm USD Fork		
Front Travel	9.0 inches		
Rear Suspension	Double sided aluminum swingarm		
Rear Travel	8.5 inches		
Brakes			