























Magma Red



THE NEW **BMW R 1200 GS ADVENTURE**

UNSTOPPABLE – because it is built without compromise to handle anything the planet's roads – and off-road – can throw at it. The new, upgraded drive train delivers effortless throttle response, the new Enduro ESA suspension option ensures supreme traction and ride comfort, and the classic design has been fine-tuned so that its looks are as memorable as its performance. The new R 1200 GS Adventure. No desert, no mountain and no river can stop it. The only limit is your imagination.

	E	Ν	G	IN	
	_		ч	ш	

Emission control

Air/oil-cooled, twin-cylinder four-stroke Type boxer, single camshaft, four valves per cylinder, central counterbalance shaft

Bore x stroke 101 mm x 73 mm 1.170 cc

Capacity

105 hp (77 kW) at 7,500 rpm Max. output 115 Nm at 5,750 rpm Max. torque

Compression ratio

Fuel/engine management Electronic intake pipe injection/BMS-K electronic engine management with

overrun fuel cut-off, twin-spark ignition Regulated 3-way catalytic converter, compliant with EU-3 emission standard

PERFORMANCE/FUEL CONSUMPTION

Over 200 km/h Consumption per 100 km 4.61 at a constant 90 km/h Consumption per 100 km

at a constant 120 km/h

Fuel type Super unleaded, 95 octane (RON); also runs on 91-octane (RON) and above due to automatic knock control

ELECTRICS Alternator 720 W three-phase generator Battery 12 V/14 Ah, maintenance-free

TRANSMISSION

Clutch Hydraulically operated single-disc dry Gears 6-speed helical synchromesh gearbox

Drive

CHASSIS/BRAKES

Frame Two-section frame made up of front and rear sections with load-bearing

> engine/gearbox BMW Motorrad Telelever, stanchion

Suspension, front diameter 41 mm, central strut, spring preload mechanically adjustable between

five settings

Rear wheel location/suspension Die-cast aluminium single-sided swing arm with BMW Motorrad Paralever, WAD (travel-

related damping) strut, spring preload hydraulically and steplessly adjustable via handwheel, adjustable rebound damping

210 mm/220 mm Travel front/rear

Wheelbase 1,510 mm 89 mm Castor Steering head angle 65.2° Cross-spoke Wheels

2.50 x 19" Rim dimensions, front 4.00 x 17" Rim dimensions, rear 110/80 R 19 Tyre, front Tyre, rear 150/70 R 17

Double-disc brake system with 305-mm Brakes, front diameter floating brake discs, 4-piston fixed

Single-disc brake (265-mm diameter), Brake, rear double-piston floating caliper

BMW Motorrad Integral ABS (partially ABS integral version) available as an option,

disengageable

DIMENSIONS/WEIGHT

Seat height 910/890 mm Rider step length 2,000/1,960 mm Unladen weight, fully fuelled/road ready1 256 kg Dry weight² 223 kg Max. permitted weight 475 kg Max. load (with standard equipment) 216 kg Usable tank volume

Of which reserve Approx. 4.0 I Lenath 2.240 mm Height (excluding mirrors) 1.525 mm Width (inc. mirrors) 990 mm

Dimensions refer to unladen motorcycles as per DIN standard.

- 1. As defined in EU directive 93/93/EEC, filled with all operating fluids, fuelled to at least 90% of usable tank capacity.
- 2. Unladen weight without operating fluids.

For full details of the BMW Motorrad range of Motorcycle and Rider Equipment, speak to your

BMW Motorrad

R 1200 GS Adventure





bmw-motorrad.com/enduro