2008 BMW R 1200 GS Adventure

Front Rotor

Rear Brake

Rear Rotor

Actuation Method


12.0 inch Dual Rotors

Single, two-piston floating caliper

10.4 inch single, fixed rotor

Hydraulic, DOT 4 fluid type

MSRP: \$16,600.00* Destination charge (not included in MSRP): \$495





Engine		Wheels and Tires			
Туре	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel		2.50 x 19 cross-spoke	
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel		4.00 x 17 cross-spoke	
Displacement	1170 cc	Front Tire		110/80 x 19 tubeless	
Horsepower	105 bhp @ 7500 rpm	Rear Tire		150/70 x 17 tubeless	
Torque	85 lb/ft @ 5750 rpm	Dimensions			
Compression Ratio	12.0 :1	Overall Length		88.6 inches	
Valve Gear	Chain-driven, high cam, OHV, w/adj. rocker arms	Overall Width		37.6 inches	
Valves	2 x 36 mm intake / 2 x 31 mm exhaust	Wheelbase		59.5 inches	
Valves / Cylinder	Four	Ground Clearance		Info. Unavailable	
Engine Oil Capacity	4.2 quarts	Seat Height		35.2 inches	
Engine Management	BMW Engine Controller - BMS K	Steering Angle		63.8 degrees	
Fuel Requirement	Premium Unleaded	Front Wheel Trail		3.8 inches	
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry		492 lbs. excluding options&accessories	
Fuel Capacity	8.7 U.S. gallons including 1 gallon reserve	Weight - Wet		564 lbs. excluding options&accessories	
Charging System	720 Watts @ 14 Volts	Maximum Load		1045 lbs. GVWR	
Battery	12 Volts 14 Amps/hour low maintenance	Standard	Standard Colors		
Cooling System	Air and thermostatically controlled oil cooling	Code Price		Description	
Drivetrain	n N15 N/C			Magma Red	
Primary Drive	1:1.737	N32 N/C		Magnesium Metallic	
Clutch	180 mm dry, single plate with hydraulic actuation	Standard Equipme		nent	
1st Gear Ratio	2.37:1	771 N/C		Cross-Spoke Wheels	
2nd Gear Ratio	1.64:1	Available Equipme		nent	
3rd Gear Ratio	1.29:1	350 \$PKG	i	Chrome Exhaust Pipe	
4th Gear Ratio	1.06:1	416 \$PKG	i	Enduro ESA	
5th Gear Ratio	0.93:1	430 \$1,65	0	Safety Package (530, 630, 650)	
6th Gear Ratio	0.84:1	431 \$950		Equipment Package 1 (350, 519, 539, 562)	
Final Drive System	Enclosed driveshaft with two universal joints	432 \$1,89	5	Equipment Package 2 (350, 416, 519, 539, 562, 680)	
Final Drive Ratio	2.91:1	519 \$PKG	i	Heated Hand Grips	
Frame and Suspension		530 \$PKG	i	Tire Pressure Monitoring (TPM)	
Frame	Tubular steel trellis frame	539 \$PKG	i	On Board Computer	
Front Suspension	BMW Telelever	562 \$PKG	i	Peripheral Headlights	
Front Travel	8.3 inches	603 \$395.	00	Anti-Theft Alarm	
Rear Suspension	BMW EVO Paralever	630 \$PKG	i	Integral ABS II (Disconnectable)	
Rear Travel	8.7 inches	630 \$1100	0.00	Integral ABS II (Disconnectable)	
Brakes		650 \$PKG	i	ASC	
Brake System	BMW	680 \$PKG	i	Saddle Bag Mounts for alu cases	
Front Brakes	Two, four-piston fixed calipers				
	I				